

# **PEELAWAY**

## PAINT REMOVAL SYSTEM

Celebrating 20 years!

### HOW TO DO A TEST PATCH

1. Use our 300g trial pack to apply a test patch evaluation before every job, as there are many different types of paint and surface conditions. Both PA1 and PA8 are available for this purpose. A recommended test patch size is that of an A4 sheet of paper.
6. By sliding the spatula behind the paper, ease off the paint, paste and paper in one piece. Remove in small sections and scrape off loose debris and residue. Place in thick plastic tie up bags.



2. Apply the paste between 2mm—3mm thick with the supplied spatula, covering evenly.
3. Cover with the Peel Away laminated paper supplied in the kit. (Can cut paper to any shape or size). Smooth over well.
7. Thoroughly wash the surface with plain water, nylon brush and sponge.



4. Tape up edges with masking tape as shown.
5. Leave on the surface for 24 hours to 72 hours, depending on the number of layers and age of coating.

8. After cleaning is complete, test patch (below) shows a successful strip.



**PEELAWAY** AUSTRALIA – ASIA PACIFIC PTY LTD  
DIVISION OF BLD CARE AUSTRALIA PTY LTD  
ABN 87 003 914 038

Unit 43 Homebush Business Village 11-21 Underwood Rd, Homebush NSW 2140  
Ph: 02 9746 6733 Fax: 02 9746 5322 Website: [www.peelaway.com.au](http://www.peelaway.com.au) Email: [peelawayau@pacific.net.au](mailto:peelawayau@pacific.net.au)