LAMINEX® CLIPWALL™ WALL PANEL SOLUTIONS





Laminex® Clipwall™ is a revolutionary wall-lining system that allows you to incorporate stunning patterns and textures into your interior walls with ease. Perfectly suited for larger walls and feature walls, it offers a time saving, durable and virtually seamless solution that is up to five times faster to install

because it is completely pre-finished. Laminex Clipwall eliminates messy installation steps such as plaster joining and painting.





PRODUCT BENEFITS

The Laminex® Clipwall™ system consists of 10mm thick MDF panels that are 600 x 2785mm, designed to clip seamlessly together and fix to timber or steel framing at 600mm centres. The MDF is protected and decorated with a low maintenance, scratch resistant, colourfast and washable surface. Corner details are simple to achieve with a protective aluminium profile and silicone.



Easy Installation:

Laminex Clipwall panels are equipped with the unique and patented Uniclic® technology, which makes the panels very simple to clip together.



UV Resistant:

Laminex Clipwall is UV resistant, ensuring panels retain their colour and keep looking great.




Scratch Resistant:

Laminex Clipwall panels come with a sturdy, scratch resistant melamine layer on both sides, giving them better protection and making sure they last.



Quick Installation:

Laminex Clipwall is very quick to install onto metal or timber framing and because panels are pre finished, no time is lost in filling, sanding or painting.



Virtually Seamless System:

Patterns and textures in the decors and the fine tolerances of the Uniclic® join provide a virtually seamless join. (With plain colours and specific light conditions, a minimal join may be visible).



Splash - Proof:

The melamine protective layer protects the panels from superficial contact with water and splashing liquid.



Hygienic Surface:

Laminex Clipwall is easy to keep hygienic, as the melamine surface is sealed and wipeable, making it easy to clean.



Fire Resistant Options:

Clipwall is also available in Group 2 options for commercial spaces that require higher fire resistant materials.



Instant Decoration:

Laminex Clipwall Deco can be digitally printed, painted, screen printed or covered with vinyl, textiles and wallpaper – providing unlimited options for decoration.



Environmentally Friendly:

Laminex Clipwall is environmentally friendly with EI formaldehyde levels and PEFC™ labelled wood varieties.







COLOUR RANGE



Soft White



Marne Oak



Soft White Linewood



Solara Oak



Silicon



Otter Linewood




Brushed Metal



Amazonia Linewood

PANEL CONSTRUCTION CUTAWAY








TECHNICAL SPECIFICATIONS

Laminex® Clipwall™ 10mm MDF panels, PEFC certified, both sides finished with a strong melamine coating or primer coating (Deco). Two long sides with Uniclic® profile, short sides square cut. Fire resistant options to Group 2. To view the technical data sheet please visit laminex.com.au

DIMENSIONS

 $2785 \times 618 \times 10$ mm (gross) $2785 \times 600 \times 10$ mm (net)



PACKAGING

2 panels / pack Surface area 3.44m² (gross) Surface area 3.34m² (net)

ACCESSORIES

Aluminium external corner profile in natural anodised finish. Available separately.

For installation instructions, fabrication guidelines and further technical specifications contact your Laminex representative or visit laminex.com.au

Corner

STEP BY STEP PLAN



I. Position the first panel.



2. Affix it in the corner, diagonally across the panel 10mm from the panel's edge.



3. Fit the notches of the Clip profile (every 400mm).



4. Position the second panel.



5. Clip this panel firmly into the previous panel and affix it.



6. Repeat these actions for each panel.



7. Last or first panel's cut to size.



Laminex Clipwall wall panel solutions is marketed and distributed by Laminex Group Pty Limited ABN 98 004 093 092, trading as Laminex. In some cases, Laminex uses computer generated imagery (CGI) to provide graphical representations of our products where actual photos are not available. The colours and finishes of the products featured within all Laminex imagery are as close to the Laminex range as CGI, photographic lighting and our printing processes allow. Different camera angles, although not designed to be misleading, can sometimes distort actual size and distances. Laminex Clipwall wall panel solutions is no different to most other materials in that darker colours will show scratches and superficial wear and tear more readily than lighter colours. Laminex Clipwall wall panel solutions should be protected from strong, direct sunlight as continuous exposure may cause discolouration or fading to the surface. Please obtain a copy of the terms and conditions of the Laminex Clipwall wall panel solutions 7 year limited warranty from laminex.com.au. This warranty is in addition to any rights that may exist under the Australian Consumer Law. Laminex, Clipwall.