

DELTA™
CROSS-OVER COMFORT HARNESS

DELTA™ KEEPS IMPROVING BECAUSE SAFETY NEVER GETS OLD.



DURABLE, COMFORTABLE & SAFE

Continuing a tradition of cutting-edge research and design, the **DELTA™** full body harness range provides a series of enhanced features to deliver absolute safety, comfort and peace of mind.



NEW FEATURES, SAME DEPENDABLE RELIABILITY

Ideal for use in roof construction, maintenance and ladder access work.

DELTA™ CROSS-OVER COMFORT HARNESS

Features:

- Lightweight aluminium hardware for reduced weight and greater comfort
- Large rear fall arrest rated D-ring for fast, easy and safe connections to fall protection system
- Fall arrest rated frontal D-ring for work positioning or rescue
- Corrosion resistant hardware for harsh work environments
- Quick-connect buckles on legs and lower shoulder strap for fast connections ensuring an exact fit every time
- Easy-adjust torso buckle for fast and easy adjustments
- Lightweight dual density foam/aerospace mesh comfort padding on shoulders, back and legs provides a durable lightweight moisture wicking and breathable padding
- Lanyard keepers provide the ideal storage solution for unanchored lanyard tails whilst working at height for ease of access and safety and break away to avoid a trip hazard
- REPEL™ Technology Webbing construction, repels liquids, naturally self-cleaning and enhances durability
- Rip stitch impact Indicator, allows the user to quickly and easily inspect the harness for impact loading
- Easy grip end tabs and keepers for fast efficient and secure web adjustment
- Fully adjustable shoulder and leg straps, for a perfect fit every time.
- Clearly labelled/identifiable attachment points
- Labels with permanent indent print conveniently located in a single location and safeguarded by a unique cover protecting vital information - donning instructions, harness data, inspection log, product certification and i-Safe™ tag
- Colour coded sizing for easy identification
- Sub pelvic strap for added security
- Exclusive no-tangle design holds the shape of the harness providing added comfort and ease of donning
- Anti roll-out design - designed to minimise the risk of roll-out when connecting a DBI-SALA® lanyard or SRL with either double locking hooks, Capital Safety patented trigger action hooks or karabiners to a large fall arrest rated D-ring
- i-Safe™ enabled to track inspections, control inventory and manage information
- Bonus harness storage bag ensures your DELTA™ harness is kept free from damage when not in use
- Available in Small, Medium, Large and Extra Large sizes
- Certified and approved to AS/NZS 1891.1

Note: Ideal harness for women

843S2016 | Small

843M2016 | Medium

843L2016 | Large

843XL2016 | Extra Large



Specifications:

Colour: Yellow/Blue. **Webbing:** REPEL™ technology webbing - 45 mm, minimum breaking load 15 kN, resistant to UV and common organic solvents (if in doubt contact manufacturer). **Thread:** polyester **Hardware:** Rear D-ring - Fall arrest rated, aluminium, minimum break strength 22.2 kN, internal diameter width - 59 mm; Front D-ring - Fall arrest rated, aluminium, minimum break strength 22.2 kN, internal diameter width - 51 mm; Quick-Connect Buckles - Hip & legs, solid riveted construction, aluminium; Chest adjuster - Spring loaded, aluminium. **Comfort Padding:** Aerospace mesh, EVA foam, nylon mesh. **Weight (approx):** 1.40 kg. **Temperature (working environment):** -20°C to 50°C (guide only). **Capacity:** 136 kg, combined weight of person, tools, clothing etc (160kg when used with a DBI-SALA Lanyard manufactured from the 1/08/2008). **Compatibility:** DBI-SALA harnesses are designed for use with DBI-SALA approved components or systems, or as recommended by a competent person. **Standards:** AS/NZS 1891.1. **Country of Origin:** Australia. **Special Instructions/Conditions of Use:** Reading user instruction manual prior to use is essential. If a dorsal extension is part of your harness the maximum lanyard assembly permitted is 1.7m or less.



Capital Safety™ - Australia & New Zealand
Australia: 1800 245 002 | New Zealand: 0800 212 505
www.capitalsafety.com.au
sales@capitalsafety.com.au

