



# Industrial Ironers

## C-Flex IL feeder



*Images shown are a representation of the product only and variations may occur.*

### Features and benefits

- One station automatic feeder for productive feeding of large flatwork on one lane
- Forward clipping supported by suction box and vacuum table for best ergonomics and productivity
- Fixed horizontal stretching blade over the full width for optimum quality of feeding
- Stop and stretch conveyor further improving quality of leading edge
- Side stretching brushes ensuring best quality of lateral edges
- Retractable clipping system for manual feeding of small flatwork on vacuum table
- Foldable trays for ergonomic feeding of small flatwork
- Neon light curtain over full width for best working conditions
- Electrolux Master Touch Screen to control the complete ironing lane from the feeder
- Central lint collecting box for a clean and safe working place
- Available in 3000 mm or 3300 mm for a perfect match with your C-Flex

### Main options

- Direct feeding into C-Flex chest for maximum quality and space saving
- Lane indication by laser beam for ergonomic manual feeding on multi lanes



Electrical and pneumatic connections	
Electrical connection	400V 3N AC 50 Hz 5.2 kW 25 A
Pneumatic connection	ø 8 mm with 7 bar pressure
Pneumatic consumption	12 l per item
Shipping data	
net, kg	1800
crated, kg	1850
Dimensions in mm	
A Width	4100
B Depth	2000
C Height	1600
D	3060
E	460
F	3300
G	600
H	780-980
I	100
J	1060
K	1290

