



WOVEN IMAGE®

DESIGN DEPARTMENT - PRODUCT SPECIFICATION SHEET

ISSUE DATE: 21.3.16

DESIGN NAME:	EchoPanel®Mura Haku
DESIGNER:	Akira Isogawa
ORIGIN:	Australia/China
COLOURS:	2
COMPOSITION:	100% PET (60% recycled) Foil Print
WIDTH:	1210mm +/- 5mm
THICKNESS:	1.9mm +/- 0.25mm
WEIGHT:	423.5g/lin.m, 350g/m ² +/- 10%
PATTERN REPEAT:	Vertical: 20cm, Horizontal: 14.5cm See wovenimage.com for pattern match and application guide
FABRIC PROTECTION:	Available on request
PIECE LENGTH:	25m roll
MINIMUM ORDER:	25m
MINIMUM FOR SPECIALS:	800m/colour

PERFORMANCE

COLOUR FASTNESS TO LIGHT:	ISO 105 B02 Rating: 6
COLOUR FASTNESS TO RUBBING:	ISO 105-X12 Rating: Wet: 4, Dry: 4/5
FIRE TEST:	AS3837 Classification: Group 1 (adhered to plasterboard) BS476 Part 7: Class 2 (adhered to Gyprock EC08™ Fire) ASTM E84: Class 1 (adhered to plasterboard)
ACOUSTICS:	AS/ISO 354 2006 NRC Value: 0.10
CARE:	See additional care instructions



USE:	
VOC EMISSIONS:	ASTM D5116 Rate: < 0.031mg/m ² /hr (7 days)
ENVIRONMENTAL:	EchoPanel® Mura achieves GreenTag Certification LCARate: Bronze, GreenRate: Level B

