Product Data Sheet



Type/Item No: ST90 Wing streetlight

Features:

LED Streetlight flying wing. The streamline design and sport style highlights its special individuality. Applying multi-chip module combined technology the LED light sources can be replaced or serviced. With inbuilt optical sensor that reduces the output by 50% when no movement is sense. A major energy saving feature as standard. The Bat Wing photometric system accurately delivers rectangle light spot and insures uniform luminance. Manufactured from pressure die-cast aluminium alloy (ADC12) offering **IP65** protection. The LED driver has short circuit protection, open circuit protection, and over heat protection CREE LED's are integrated into the electroplated reflector with 94% efficiency









Optical sensor control. Reduces the power to 50% when nobody passes by, and increases to 100% when someone passes within the 10 metre sensing range


Class:	IP	Colour:
1	65	Silver

Lamp:

48 x 1.5w Cree LED

Gear:

LED Driver Integral rear mounted COMPLIANCES:		
Magnetic Emission	EN55015	
Harmonic	EN61000-3-2	
Flicker	EN61000-3-3	
Immunity	EN61547	
Safety	EN61347-1	
Tested to IEC	61347-2-13(LED control gear)	



Luminous Flux Luminous Efficacy Output Power LED source Colour Temperature CRI 6206 lm 72 lm/w 86w 48 6500K >70



CE



Dimensions:

1/19 Macquaire Drive, Thomastown, Vic. 3074 T: 0394646642 F: 0394645504. www.designlite.com.au Email: sales@designlite.com.au