


DESIGN NAME	EchoPanel® 24mm
DESIGNER:	Woven Image
ORIGIN:	Australia
COLOURS:	10
WEAVE:	Non woven
COMPOSITION:	100% PET (60% recycled)
PANEL DIMENSIONS:	2400mm (+/-5mm) x 1820mm (+/-10mm)
WEIGHT:	3,000g/m ² +/-10%
THICKNESS:	24mm +/- 7%

PERFORMANCE

COLOUR FASTNESS TO LIGHT:	ISO 105-B02-1994 Rating: 6-7
FIRE TEST:	ISO 9705: Group 1 ASTM E84Unadhered: B or Class 2 BS EN 13501.1: Classification B-s1, d0
FABRIC CARE:	Blot excess spills from material quickly. Wipe with a damp cloth. If stain persists, apply small quantities of carpet or upholstery shampoo solution with a damp cloth. Blot well with a clean cloth after each application of the solution. Warning, avoid excessive amounts of water. Ensure adequate ventilation if the product is likely to be subject to excessive moisture.
SOUND ABSORPTION:	AS ISO 354 – 2006 NRC Value: 0.65 (with no air gap) NRC Value: 0.75 (with 20mm air gap) NRC Value: 0.85 (with 50mm air gap)
VOC EMISSIONS:	ASTM D5116 Rate: < 0.02 mg/m ² /hr (7 days)
ENVIRONMENTAL:	 EchoPanel® achieves GreenTag Certification GreenRate: Level A



DESIGN NAME	EchoPanel®
DESIGNER:	Woven Image
ORIGIN:	Australia
COLOURS:	31
WEAVE:	Non woven
COMPOSITION:	100% PET (60% recycled)
PANEL DIMENSIONS:	2800mm (+/-10mm) x 1200mm(+/-5mm)
WEIGHT:	2400g/m ² +/-10%
THICKNESS:	12mm +/- 7%


PERFORMANCE

COLOUR FASTNESS TO LIGHT:	ISO 105-B02-1994 Rating: 6-7
FIRE TEST:	AS 1530.3 ISO 9705: Group 1 GB8624 B1 BS EN 13501.1: Classification B-s1, d0
FABRIC CARE:	Blot excess spills from material quickly. Wipe with a damp cloth. If stain persists, apply small quantities of carpet or upholstery shampoo solution with a damp cloth. Blot well with a clean cloth after each application of the solution. Warning, avoid excessive amounts of water. Ensure adequate ventilation if the product is likely to be subject to excessive moisture.
SOUND ABSORPTION:	AS ISO 354 – 2006 NRC Value: 0.45 (with no air gap) NRC Value: 0.60 (with 20mm air gap) NRC Value: 0.75 (with 50mm air gap)
VOC EMISSIONS:	ASTM D5116 Rate: < 0.02 mg/m ² /hr (7 days)
ENVIRONMENTAL:	EchoPanel® achieves GreenTag Certification GreenRate: Level A



DESIGN NAME:	EchoPanel® 7mm
DESIGNER:	Woven Image
ORIGIN:	Australia
COLOURS:	5
WEAVE:	Non woven
COMPOSITION:	100% PET (60% recycled)
PANEL DIMENSIONS:	2800mm (+/- 10mm) x 1200mm (+/- 5mm)
WEIGHT:	1400g/m ² +/- 10%
THICKNESS:	7mm +/- 7%

PERFORMANCE

COLOUR FASTNESS TO LIGHT:	ISO 105-B02-1994 Rating: 6-7
FIRE TEST:	ISO 9705: Group 1 AS 1530.3 BS 476: Part 7 Class 2
FABRIC CARE:	Blot excess spills from material quickly. Wipe with a damp cloth. If stain persists, apply small quantities of carpet or upholstery shampoo solution with a damp cloth. Blot well with a clean cloth after each application of the solution. Warning, avoid excessive amounts of water. Ensure adequate ventilation if the product is likely to be subject to excessive moisture.
SOUND ABSORPTION:	AS ISO 354 – 2006 NRC Value: 0.25 (with no air gap) NRC Value: 0.45 (with 20mm air gap) NRC Value: 0.70 (with 50mm air gap)
VOC EMISSIONS:	ASTM D5116 Rate: < 0.02 mg/m ² /hr (7 days)
ENVIRONMENTAL:	 EchoPanel® achieves GreenTag Certification, GreenRate: Level A

