

Neoflex™ 800 Series Specification

Neoflex™
RESILIENT FLOORING

REPHOUSE
www.rephouse.com



Your supreme floor awaits.

Available in 20 solid EPDM colors, Neoflex™ 800 Series is ideally suited as a monolithic flooring statement. It is also very popular for borders, highlights and logos in conjunction with our other floors.

SPECIFICATIONS

Thickness	3 - 12 mm (1/8" - 1/2")	
Roll Length	10 -25 m (50')	
Roll Width	1.2 m (4')	
Density	± 1,300 kg/m ³ (81.04 lbs/cu. ft.)	
Resilience	40%	DIN 18032-2
Tensile Strength	0.91 N/mm ²	DIN 18032-2
Tear Strength	9.7 N/mm	ASTM D624
Taber Abrasion	0.66 gr	ASTM C504
Shore Hardness A	60	ASM D2240
Remaining Indentation	0.05 mm	DIN 53960
Noise Absorption	13dB [4 mm]	EN 20140/ISO 140
Flammability	Bfl-s1	EN 13501
	Class 1	ASTM E648
Coefficient of Friction	Dry 1.1, Wet 1.03	ASTM D2047-97
Slip Resistance	R10	ANZS 4596:1999
Thermal Stability	-40°C to 100°C	ASTM C1026



www.rephouse.com