

ProStep[®] Safeline (SL)

Working hard to keep
the world on its feet

ProStep[®] SL - Safety Stair Nosing

ProStep[®] SL features the ProStep[®] characteristics of high safety, ease of installation and durability it is manufactured from reinforced tempered aluminium extrusion, milled into a straight faced anodised finish to provide a long term, attractive safe solution.

ProStep[®] SL includes the SafeLine range of anti-slip peel and stick tapes which combine aluminium oxide and a thick plastic carrier to provide a flexible yet durable anti-slip solution. The inserts are formulated to resist water, steam and detergent and will withstand continuous temperatures in the range -30°C to 120°C. ProStep[®] SL safety stair nosing are pre-cut to length and pre-drilled, and are supplied with fixing screws and star plugs.

ProStep[®] SL is designed to meet the requirements of AS1428.4 and is available with a range of high visibility SafeLine anti-slip inserts to provide a safe environment

DIMENSIONS:

Designed to conform to the Australian Standards, ProStep[®] Safety Stair Nosings

- have a combined insert depth of 50mm.
- are supplied predrilled, counter sunk and cut to length, ready to install.

Product Range: ProStep[®] SL is available with either black, grey, yellow or combination SafeLine anti-slip inserts and are R13 rated to provide maximum safety.

FEATURES:

- Designed and manufactured from reinforced tempered aluminum extrusion to provide maximum strength and long term durability.
- Supplied milled and anodized to provide an attractive and safe solution.
- Supplied with an R13 SafeLine anti-slip insert for maximum safety.
- Exceeds the anti-slip requirements of Australian Standards AS4586.
- Supplied pre-drill, counter sunk and cut to length, ready to install.
- Are supplied with all necessary stainless steel fixing screws and anchors to ensure longevity.
- Can be retro-fitted on to concrete, ceramic tiles, timber, carpet(direct stick) and most other surfaces.
- Are easy to install with no fuss - ideal for home DIY applications.
- SafeLine inserts are available as spares and are easily replaced in the event of damage.



APPLICATIONS:

ProStep[®] SL safety stair nosing is particularly suitable for pedestrian traffic in internal flooring surfaces prone to water or oil spillage such as: concrete and other hard surface applications, including direct stick carpet.

LUMINANCE CONTRAST:

In accordance with the Australian Standards a minimum luminance contrast of 30% must be provided between the stair nosing and surrounding substrate. ProStep[®] SL is available in 3 basic colours which allow specifiers to select the most appropriate luminance contrast for any given application and aesthetic requirement.

COMPLIES WITH:

1. AS/NZS 1428:4.2002 Design for access and mobility.
2. AS/NZS 4586:1999 Slip resistance classification for new pedestrian surface materials.

www.cobbletac.com