



SOLATUBE
Innovation in Daylighting™

Solatube Australia Pty Ltd
ABN 76 144 716 316
P O Box 6689 Wetherill Park NSW 2164
Phone: 13 16 19 www.solatube.com.au

Ventilation Add-On Kit

The Solatube 160 DS is available with an optional Ventilation Add-On Kit. When combined with this innovative accessory, the 2-in-1 ceiling fixture minimises ceiling penetrations for a more attractive look.



*Vent cap appearance may vary for different roof types.



SPECIFICATIONS: Ventilation Add-On Kit

Fan Motor Assembly:	100 mm in-line
Motor:	Thermally protected
Supply:	115 volt – 60Hz or optional 220-240 volt – 50Hz
Amps:	0.24 Amp or optional 220-240 volt – 0.13 Amp
Airflow:	52 l/s (litres per second)
Insulation:	IC (Insulation may contact Fan Motor Assembly)
Moisture:	Suitable for wet or damp locations
TUV Certifications	115V: cNRTLus NRTL “Nationally Recognised Testing Laboratories” according to UL 507
Reduced noise:	65.3db (115V)

Flexible Duct:

- 1) 100 mm diameter air duct (Class 1).
- 2) Local building codes may require air duct (Class 0) for certain fire-rated installations.

Installation:

- 1) Service access is required to the Fan Motor Assembly Junction Box.
- 2) Space requirements: Minimum 12 1/2 in (320 mm) between ceiling joists and minimum 12 in (300 mm) vertical clearance above ceiling is required.
- 3) Ventilation fan should remain on for a minimum of 10 minutes in a bathroom after a shower.